

30-Gallon & Base-Mount

Air Compressors



Designed with a powder coated ASME receiver tank, you will experience proven performance from the 30-gallon and base-mount air compressors time after time.

COMPRESSOR PUMP

- Cast iron compressor pump
- Splash lubricated
- Stainless-steel braided discharge hose
- Large canister intake filter
- · Oil level sight indicator

FRAME

- Powder coated ASME receiver tank
- 3/16-inch base plate to reduce vibration
- Powder coated two-piece belt guard
- Removable base plate offers flexible installation

COMPONENTS

- Regulator and two gauges for tank and outlet pressure
- Manual drain valves for proper maintenance
- 16½-inch fly wheel
- Quality pilot valve unloader

LIMITED WARRANTY

• 3 year engine

CERTIFICATION

ASME Boiler and Pressure Vessel Code – UM



30-Gallon & Base-Mount

Air Compressors - Two Stage - Gasoline

STATIONARY MODELS

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM2-SH09-30M	17.2 @ 175	270cc Honda GX270 OHV+	30-gallon	Pneumatic	40.5x17.5x44.5in.	446 lb.	376 lb.
AM2-SH09-30ME^	17.2 @ 175	270cc Honda GX270 OHV+	30-gallon	Pneumatic	40.5x17.5x44.5in.	460 lb.	390 lb.
AM2-SM09-30M	17.2 @ 175	300cc Mi-T-M OHV	30-gallon	Cable throttle	40.5x17.5x44.5in.	434 lb.	364 lb.
AM2-SM09-30ME^	17.2 @ 175	300cc Mi-T-M OHV	30-gallon	Cable throttle	40.5x17.5x44.5in.	449 lb.	379 lb.

⁺⁴⁹ state engine. Not for sale in California.

BASE-MOUNT MODEL

MODEL NUMBER	CFM @ PSI*	DISPLACEMENT/ENGINE	TANK SIZE	ENGINE IDLE CONTROL	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
AM2-SM09-B^	17 2 @ 175	300cc Mi-T-M OHV	Base-mount	Cable throttle	36 5x21x32in	379 lb	309 lb

[^]Equipped with electric start - battery, box and cables not included.

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
854-0093	Service truck mount kit – Includes four rubber isolators to reduce wear. Recommended for models mounted in service truck applications	
AW-6000-1002	Equipment cover — Keeps your equipment clean, dry and looking like new	All models

OPTIONS:

OI HOING.		
PART NUMBER	DESCRIPTION	FITS MODELS
AX-0003	Manual drain/regulator/metal bowl – Drains moisture from air system	All models
AX-0017	Battery, battery tray, box and 2-foot of cables - Attaches to engine side of unit	Electric start models
AX-0077	Battery tray, box and 2-foot of cables – Attaches to engine side of unit	Electric start models
IX-0055	Remote start/choke – 7-foot wire extension for key switch	AM2-SH09-30ME
IX-0059	Remote start/choke, sealed cable – 7-foot wire extension for key switch	AM2-SH09-30ME
IX-0067	Remote start/choke, sealed cable – 7-foot wire extension for key switch	AM2-SM09-30ME

^{*}Equipped with 150-PSI maximum rated regulator.