



WTP-F03-1MGME

Polypropylene housings make these pumps suitable for corrosive environments and ideal for agricultural fertilizer and chemical applications.

COMPONENTS

- Poly impellers with stainless-steel inserts can handle solid suspended particles up to 3/8-inch diameter (WTP-F02-1MGM has nylon impellers)
- Polypropylene housing suitable for corrosive environments
- Self-priming capabilities with maximum suction lift up to 25-foot
- EPDM mechanical seal and inlet valve for longevity and reliability

LIMITED WARRANTY

- 3 year engine

MODEL NUMBER	SUCTION DISCHARGE SIZE	MAXIMUM GPM	MAXIMUM PSI	MAXIMUM SUCTION LIST	DISPLACEMENT/ENGINE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
WTP-F02-1MGM	2in.x2in.	220	58	25ft.	212cc Mi-T-M OHV	18.5x18.5x14in.	51 lb.	42 lb.
WTP-F03-1MGME	3in.x3in.	440	54	25ft.	420cc Mi-T-M OHV with electric start – battery not included	23.5x19.5x17.5in.	102 lb.	93 lb.

2 & 3-Inch Chemical/Liquid Fertilizer Pumps

Water Pumps

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
15-0306	20-foot x 2-inch PVC suction hose with poly C&E fittings	WTP-F02-1MGM
55-0054	2-inch poly male adapter F	WTP-F02-1MGM
55-1895	2-inch spoly female adapter B	WTP-F02-1MGM
70-0550	2-inch replacement chemical pump seal kit	WTP-F02-1MGM
15-0307	20-foot x 3-inch PVC suction hose with poly C&E fittings	WTP-F03-1MGME
55-2288	3-inch poly male adapter F	WTP-F03-1MGME
55-2289	3-inch spoly female adapter B	WTP-F03-1MGME
70-0551	3-inch replacement chemical pump seal kit	WTP-F03-1MGME



3-inch pump accessories shown:
20-ft. x 3-in. PVC suction hose with poly C&E fittings, 15-0307; 3-in. poly male adapter F, 55-2288; and 3-in. poly female adapter B, 55-2289

 **WARNING:** Cancer and Reproductive Harm - www.P65Warnings.ca.gov.