

Electric — Portable — Belt Drive



DC-4004-W1E3G

With up to 5000-PSI of cleaning power, this series is used for paint preparation and mold and mildew removal around commercial facilities, barns and large workshops.

PUMP

- External bypass system protects from heat build-up
- Factory preset unloader (All models except DC-5004-W0E3G)
- Forged brass manifold (Nickel plated brass on DC-4004-W1E3G)
- Thermal relief valve
- Water filter with clear sleeve for screen inspection

MOTOR

- Totally enclosed fan-cooled electric motor with thermal overload protection
- 10-foot power cord

FRAME

- Powder coated steel frame and base plate with 1-inch tube handles
- Totally enclosed belt guard
- 13-inch flat-free tires

COMPONENT

- Heavy-duty dual cogged belt drive system

UNIT INCLUDES

- Quick connect nozzles – 0°, 15°, 25° and 40°
- 50-foot x 3/8-inch non-marking high pressure hose
- 36-inch lance with rubber grip (48-inch on DC-4004-W1E3G and DC-5004-W0E3G)
- Professional-grade insulated trigger gun with safety lock-off

LIMITED WARRANTY

- 1 year electric motor



Premium Series

Cold Water – Electric – Portable – Belt Drive

MODEL NUMBER	PSI	GPM	HORSEPOWER/MOTOR	PUMP	PLUG TYPE	DIMENSIONS (LxWxH)	SHIP WT.	NET WT.
DC-2405-W5E2G	2400	4.6	8.0 HP, 230V, 1Ø, 34.6A	General	NEMA 6-50P	46x32.5x30in.	405 lb.	322 lb.
DC-2405-W4E3G*	2400	4.6	8.0 HP, 230V, 3Ø, 20.0A or 8.0 HP, 460V, 3Ø, 10.0A	General	NEMA L15-30P	46x30x30in.	384 lb.	318 lb.
DC-3004-W5E2G	3000	3.5	8.0 HP, 230V, 1Ø, 34.6A	General	NEMA 6-50P	46x32.5x30in.	405 lb.	322 lb.
DC-3004-W4E3G*	3000	3.5	8.0 HP, 230V, 3Ø, 20.0A or 8.0 HP, 460V, 3Ø, 10.0A	General	NEMA L15-30P	46x30x30in.	384 lb.	318 lb.
DC-3005-W0E2G	3000	4.8	10.0 HP, 230V, 1Ø, 41.5A	General	NEMA 6-50P	46x32.5x30in.	470 lb.	396 lb.
DC-3005-W0E3G*	3000	4.8	10.0 HP, 230V, 3Ø, 26.0A or 10.0 HP, 460V, 3Ø, 13.0A	General	NEMA 15-50P	46x32.5x30in.	450 lb.	376 lb.
DC-4004-W1E3G*	4000	3.9	15.0 HP, 230V, 3Ø, 40.0A or 15.0 HP, 460V, 3Ø, 20.0A	General	NEMA 15-50P	46x32.5x30in.	505 lb.	431 lb.
DC-5004-W0E3G*	5000	4.0	15.0 HP, 230V, 3Ø, 40.0A or 15.0 HP, 460V, 3Ø, 20.0A	General	NEMA 15-50P	46x32.5x30in.	505 lb.	431 lb.

*460V motors available as options.

ACCESSORIES:

PART NUMBER	DESCRIPTION	FITS MODELS
50-0161	High pressure detergent injector – High pressure water mixes with detergent to clean even the heaviest build-up	All models
851-0317	50-foot x ¾-inch non-marking hose – For when you need extra hose for added mobility	DC-5004-W0E3G
851-0338	50-foot x ¾-inch non-marking hose – For when you need extra hose for added mobility	2400 to 4000-PSI models
AW-7510-Series	Rotating nozzle – Increase your cleaning power and decrease your cleaning time, 5100-PSI rated	All models
AW-8400-0021	Low pressure detergent injector – Allows the user to apply the recommended detergents	All models

OPTIONS:

PART NUMBER	DESCRIPTION	FITS MODELS
CX-0005	36-inch insulated dual lance – Has high and low pressure tips that allow you to switch to the low pressure detergent injector without having to change tips	DC-2405, DC-3004 & DC-3005 models
CX-0003	460V on 8.0-HP, 3Ø models – When 460V of power is available	DC-2405-W4E3G & DC-3004-W4E3G
CX-0062	460V on 10.0-HP, 3Ø models – When 460V of power is available	DC-3005-W0E3G
CX-0057	460V on 15.0-HP, 3Ø models – When 460V of power is available	DC-4004-W1E3G & DC-5004-W0E3G
CX-0093	Stationary option – This option will remove the existing tall handle and wheels, which will be replaced with a short handle and rubber feet for stationary applications	DC-2405 & DC-3004 models
CX-0094	Stationary option – This option will remove the existing tall handle and wheels, which will be replaced with a short handle and rubber feet for stationary applications	DC-3005, DC-4004 & DC-5004 models



NEMA 6-50P,
50-amp plug



NEMA L15-30P,
30-amp plug



NEMA 15-50P,
50-amp plug



WARNING: Cancer and Reproductive Harm - www.P65Warnings.ca.gov.